



## SELECTION & SPECIFICATION DATA

<b>Type</b>	Modified Bitumen Membrane Adhesive
<b>Description</b>	Blackhawk 5501 Roofing Adhesive is an asphaltic adhesive specially designed to adhere modified bitumen membranes. Blackhawk 5501 Roofing Adhesive is formulated to be used as a squeegee- or spray-grade modified bitumen roofing membrane adhesive.
<b>Features</b>	<ul style="list-style-type: none"> <li>• Cold-applied</li> <li>• Quick drying</li> <li>• Low odor</li> <li>• Single-component</li> <li>• Strong cold-weather bond</li> <li>• Excellent wind uplift resistance</li> </ul>
<b>Uses</b>	Adhesive for single and multi-ply SBS roofing membranes.
<b>Color</b>	Black
<b>Primer</b>	Self-priming
<b>Solids Content</b>	80 ± 2% by weight
<b>VOC</b>	<250 g/l (2.09 lb/gal)

## SUBSTRATES & SURFACE PREPARATION

<b>All</b>	All surfaces must be clean and free from anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
------------	---

## SAFETY

<b>Safety</b>	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
---------------	--

## MIXING & THINNING

<b>Mixing</b>	No mixing required
<b>Thinning</b>	Do not thin
<b>Cleanup</b>	Mineral spirits or equivalent solvent.

## APPLICATION GUIDANCE

<b>Airless Spray Single Leg</b>	Pump size: 45:1 or greater Hose length: 200 ft x 3/4-inch ID Whip length: 15 ft x 1/2-inch ID
<b>Squeegee</b>	Serrated, 1/4-inch

## PACKAGING, ESTIMATING & HANDLING

ITEM #	PACKAGING
K-5501-005-001	Pail - 4.7 gallons
<b>Theoretical Coverage Rate</b>	1.5 – 2 gallons per square depending on substrate
<b>Storage &amp; Shelf Life</b>	Estimated shelf life is 12 months when stored in a dry area at 75°F (24°C). Actual shelf life may vary with storage conditions. Do not store below 40°F (4°C) or above 110°F (43°C). Store indoors. This product is not affected by excursions below published storage temperatures. Always inspect the product prior to use to make sure it is smooth and homogeneous.

Rev 12/21



### TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.