

1. Identification

Product identifier	BLACKHAWK™ 5164 ASPHALT PRIMER
Other means of identification	None.
Recommended use	Not available.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Company Name	ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.
Address	2829 Lakeland Drive Jackson, MS 39232 USA
After hours telephone number	1-800-222-7122
Normal work hours telephone number	1-877-982-7667
Website	www.ergonarmor.com
E-mail	sds@ergon.com
Emergency 24-hour telephone number	CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887
Information on operation hours	8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 1
	Carcinogenicity	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Causes serious eye irritation. May cause genetic defects. May cause drowsiness or dizziness. Causes skin irritation. May cause cancer.
Precautionary statement	
Prevention	Keep container tightly closed. Ground/bond container and receiving equipment. Wash thoroughly after handling. Avoid release to the environment. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Obtain special instructions before use. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood.

Response	In case of fire: Use CO ₂ , dry chemical, or foam for extinction. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before re-use. If skin irritation or redness occur: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical assistance if you feel unwell. Call a poison center/doctor if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	60 - 70
PROPRIETARY INGREDIENTS		N/A	30 - 40

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. If symptoms persist, get medical attention. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Wash contaminated clothing before reuse. Get medical attention if irritation develops or persists.
Eye contact	IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.
Ingestion	Do NOT induce vomiting. Do not give liquids. Rinse mouth thoroughly. Get medical attention immediately. Never give anything by mouth to a victim who is unconscious or is having convulsions. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Swelling. Itching. Skin irritation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Causes eye irritation. May cause redness and pain. Dermatitis. Burning sensation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid and vapor. May react with strong oxidizer, increasing the risk of fire or explosion. Vapors may form explosive mixtures with air.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Water runoff can cause environmental damage. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods

In the event of fire, cool tanks with water spray. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

General fire hazards

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing mist or vapor. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with DRY earth, DRY sand, or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Ventilate area and avoid breathing vapors or mist. Clean surface thoroughly to remove residual contamination. Keep in suitable, closed containers for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not ingest. Avoid breathing dust or vapor. Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Do not eat, drink or smoke when using the product. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Do not empty into drains. Observe good industrial hygiene practices. Handle empty containers with care because of residual vapors are flammable.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a well-ventilated place. Store in a cool dry place. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers closed when not in use. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit At this time, the other constituents have no known exposure limits.

U.S. - NIOSH Components

U.S. - NIOSH Components	Type	Value
ASPHALT, OXIDIZED (CAS 64742-93-4)	REL	5 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Use explosion-proof equipment. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Gas detectors should be used when flammable gases/vapors are released. Prevent electrostatic charge build-up by using common bonding and grounding techniques.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes. Chemical goggles are recommended.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. Impervious gloves.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Chemical resistant gloves.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Shower, hand and eye washing facilities near the workplace are recommended.

9. Physical and chemical properties

Appearance	Brown to black in color.
Physical state	Liquid.
Form	Liquid.
Color	Dark brown Black.
Odor	Hydrocarbon-like.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	245 - 300 °F (118.33 - 148.89 °C)
Flash point	45.0 - 70.0 °F (7.2 - 21.1 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 9.90 mm Hg (at 70°F/21.1°C)
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.91

VOC 345 g/l

10. Stability and reactivity

Reactivity This product may react with oxidizing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Not known.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials. Protect against direct sunlight. Extremes in temperature.

Incompatible materials Strong acids. Strong oxidizing agents. Strong bases.

Hazardous decomposition products Carbon oxides. Sulfur dioxide. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May irritate and cause redness and pain.

Eye contact Causes serious eye irritation.

Ingestion May be harmful if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not classified.

Skin corrosion/irritation Causes skin irritation. Defatting, drying and cracking of skin. Irritating and may cause redness and pain.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Not available.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Not expected to be hazardous by OSHA criteria. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

UN number UN1999
UN proper shipping name Tars, liquid including road oils and cut back bitumens
Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
Packing group III
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions B1, B13, IB3, T1, TP3
Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1999
UN proper shipping name Tars, liquid including road asphalt and oils, bitumen and cut backs
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards No.
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1999
UN proper shipping name TARS, LIQUID including road oils, and cutback bitumens

Transport hazard class(es)**Class** 3**Subsidiary risk** -**Packing group** III**Environmental hazards****Marine pollutant** No.**EmS** F-E, S-E**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.**DOT****IATA; IMDG****15. Regulatory information**

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.
 CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Yes**Hazardous chemical**

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Germ cell mutagenicity
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ASPHALT, OXIDIZED (CAS 64742-93-4)

Listed: January 1, 1990

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	11-17-2020
Revision date	11-22-2021
Version #	05
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA ratings	Health: 2 Flammability: 3 Instability: 0

References

ACGIH
 ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
 EPA: AQUIRE database
 HSDB® - Hazardous Substances Data Bank
 IARC Monographs. Overall Evaluation of Carcinogenicity
 National Toxicology Program (NTP) Report on Carcinogens
 NLM: Hazardous Substances Data Base
 US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Physical & Chemical Properties: Multiple Properties
GHS: Classification